



*ENCODERS are stocked with: 12, 24, 72, 120, 240, and 360 inch cables. The Model 250 is supplied with a 120 inch cable if no specification is made.

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ACCURATE TECHNOLOGY, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ACCURATE TECHNOLOGY IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE	ACCURATE TECHNOLOGY INC
DIMENSIONS ARE IN MM TOLERANCES: ANGULAR: MACH±1 BEND ±2 ONE PLACE DECIMAL ±0.02 TWO PLACE DECIMAL ±0.01		DRAWN MF	1/1/2011	
INTERPRET GEOMETRIC TOLERANCING PER:		CHECKED		TITLE:
MATERIAL		ENG APPR.		ProScale Model 250
FINISH		MFG APPR.		SIZE A DWG. NO. Installation Dimensions REV A
DO NOT SCALE DRAWING		Q.A.		SCALE: 1:3 WEIGHT: SHEET 1 OF 2
		COMMENTS:		

HOLE TABLE FOR MODEL 250

Dimensions subject to change
Dimensions are +/- 0.020 tolerance.

MODEL	PHYSICAL LENGTH	MEASURING LENGTH	DIMENSION A	DIMENSION B	TOTAL HOLES
250-2	28 inches	24 inches	2 inches	12 inches	6
250-4	56 inches	52 inches	4 inches	12 inches	10
250-5	64 inches	60 inches	2 inches	30 inches	6
250-8	100 inches	96 inches	2 inches	16 inches	14
250-10	124 inches	120 inches	6 inches	16 inches	16
250-15	184 inches	180 inches	7 inches	17 inches	22
250-20	244 inches	240 inches	5 inches	18 inches	28