



\*ENCODERS are stocked with: 12, 24, 72, 120, 240, and 360 inch cables. The Model 250 is supplied with a 120 inch cable if no specification is made.

PROPRIETARY AND CONFIDENTIAL THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ACCURATE TECHNOLOGY, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ACCURATE TECHNOLOGY IS PROHIBITED.

UNLESS OTHERWISE SPECIFIED:		NAME	DATE
DIMENSIONS ARE IN MM		DRAWN	MF 1/1/2011
TOLERANCES:		CHECKED	
ANGULAR: MACH ±1 BEND ±2		ENG APPR.	
ONE PLACE DECIMAL ±0.02		MFG APPR.	
TWO PLACE DECIMAL ±0.01		Q.A.	
INTERPRET GEOMETRIC TOLERANCING PER:		COMMENTS:	
MATERIAL			
FINISH			
DO NOT SCALE DRAWING			

NAME	DATE
MF	1/1/2011
CHECKED	
ENG APPR.	
MFG APPR.	
Q.A.	
COMMENTS:	

ACCURATE TECHNOLOGY INC		
TITLE:		
ProScale Model 250		
SIZE	DWG. NO.	REV
A	Installation Dimensions	A
SCALE: 1:3	WEIGHT:	SHEET 1 OF 2

5

4

3

2

1

# HOLE TABLE FOR MODEL 250

Dimensions subject to change  
Dimensions A and B are +/- 0.020 tolerance.

MODEL	PHYSICAL LENGTH	MEASURING LENGTH	DIMENSION A	DIMENSION B	TOTAL HOLES
250-2	28 inches	24 inches	2 inches	12 inches	6
250-4	56 inches	52 inches	4 inches	12 inches	10
250-5	64 inches	60 inches	2 inches	30 inches	6
250-6	76 inches	72 inches	6 inches	16 inches	10
250-8	100 inches	96 inches	2 inches	16 inches	14
250-10	124 inches	120 inches	6 inches	16 inches	16
250-12	148 inches	144 inches	6 inches	17 inches	18
250-15	184 inches	180 inches	7 inches	17 inches	22
250-20	244 inches	240 inches	5 inches	18 inches	28