



40, 60 AND 100 INCH RANGES ON STANDARD MODELS

8.50

2.75

1.89

STEEL THUMBSCREW TO LOCK CARRIAGE.

.750 DEPTH OF RADIUSSED TIPS

.472 JAW THICKNESS

2.80

.984

R.472 JAW RADIUS

CARRIAGE STOP

DIGITAL READOUT HAS OUTPUT PORT BUILT IN. CAN BE USED WITH WIRED OR WIRELESS TRANSMITTERS.

4 PINS ARE EASILY REMOVED AND RE-INSTALLED. DIAMETER OF EACH PIN IS 12.0MM.

PINS CAN BE USED FOR MEASURING CORNER-CORNER, INSIDE-INSIDE, OR OUTSIDE-OUTSIDE (AS DESIRED)

CONE KIT - FOR HOLE TO HOLE AND HOLE TO EDGE MEASUREMENTS

UNLESS OTHERWISE SPECIFIED: DIMENSIONS ARE IN INCHES TOLERANCES: ANGULAR: MACH ±1 BEND ±2 ONE PLACE DECIMAL ±0.050 TWO PLACE DECIMAL ±0.020 THREE PLACE DECIMAL ±0.005 INTERPRET GEOMETRIC TOLERANCING PER: MATERIAL ASST. FINISH ASST. DO NOT SCALE DRAWING	DRAWN	NAME	DATE	ACCURATE TECHNOLOGY INC. TITLE: ProPanel HD/E SIZE DWG. NO. REV C 901-401x-xxx B SCALE: 1:4 WEIGHT: SHEET 1 OF 1	
	CHECKED	MF	12-29-09		
	ENG APPR.				
	MFG APPR.				
	Q.A.				
	COMMENTS:				

PROPRIETARY AND CONFIDENTIAL
 THE INFORMATION CONTAINED IN THIS DRAWING IS THE SOLE PROPERTY OF ACCURATE TECHNOLOGY, INC. ANY REPRODUCTION IN PART OR AS A WHOLE WITHOUT THE WRITTEN PERMISSION OF ACCURATE TECHNOLOGY, INC. IS PROHIBITED.